

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A method for processing a data stream comprising:
 - receiving a data segment;
 - determining whether the data segment has been previously stored; and
 - in the event that the data segment is determined not to have been previously stored, generating a unique identifier for specifying the data segment in a representation of the data stream.
2. (Original) A method for processing a data stream as recited in Claim 1 wherein determining whether the data segment has been previously stored includes generating a content derived summary.
3. (Original) A method for processing a data stream as recited in Claim 1 wherein determining whether the data segment has been previously stored includes generating a content derived summary for the data segment; and the content derived summary is a fingerprint.
4. (Original) A method for processing a data stream as recited in Claim 1 wherein determining whether the data segment has been previously stored includes looking up a content derived summary for the data segment; and the content derived summary is the data segment.
5. (Original) A method for processing a data stream as recited in Claim 1 wherein determining whether the data segment has been previously stored includes generating a content derived summary for the data segment; and locating the content derived summary in a content derived summary storage.

6. (Original) A method for processing a data stream as recited in Claim 1 wherein determining whether the data segment has been previously stored includes locating the data segment in a data segment storage.
7. (Original) A method for processing a data stream as recited in Claim 1 wherein in the event that the data segment is determined not to have been previously stored, further including storing the data segment in a data segment storage location.
8. (Original) A method for processing a data stream as recited in Claim 1 wherein:
 - determining whether the data segment has been previously stored includes generating a content derived summary for the data segment;
 - in the event that the data segment is determined not to have been previously stored, further including:
 - storing the data segment in a data segment storage location; and
 - updating a data structure for storing the content derived summary, the unique identifier, and the data segment storage location.
9. (Original) A method for processing a data stream as recited in Claim 1 wherein:
 - determining whether the data segment has been previously stored includes generating a content derived summary for the data segment;
 - in the event that the data segment is determined not to have been previously stored, further including:
 - storing the data segment in a data segment storage location; and
 - updating a data structure for storing the content derived summary, the unique identifier, and the data segment storage location; wherein
 - the data segment storage location is accessed given the unique identifier or given the content derived summary in the data structure.

10. (Original) A method for processing a data stream as recited in Claim 1 wherein:

determining whether the data segment has been previously stored includes
generating a content derived summary for the data segment;

in the event that the data segment is determined not to have been
previously stored, further including:

storing the data segment in a data segment storage location; and
updating a data structure for storing the content derived summary,
the unique identifier, and the data segment storage location; wherein
the data segment storage location is accessed given the unique
identifier or given the content derived summary, using a single access of a storage
device.

11. (Original) A method for processing a data stream as recited in Claim 1 wherein:

determining whether the data segment has been previously stored includes
generating a content derived summary for the data segment;

in the event that the data segment is determined not to have been
previously stored, further including:

storing the data segment in a data segment storage location; and
updating a data structure for storing the content derived summary,
the unique identifier, and the data segment storage location; wherein
a region of the data structure that includes the data segment storage
location is accessed given the unique identifier or given the content derived
summary, using a single access of a storage device.

12. (Currently Amended) A method for processing a data stream as recited in Claim 1, wherein the unique identifier ~~is a short identifier that~~ does not depend on probability for its uniqueness, and the unique identifier is shorter than a signature of the data segment.
13. (Original) A method for processing a data stream as recited in Claim 1, wherein the unique identifier is a serial number.
14. (Original) A method for processing a data stream as recited in Claim 1, wherein the unique identifier is derived from a hash value.
15. (Original) A method for processing a data stream as recited in Claim 1, wherein the unique identifier is an address of the data segment.
16. (Original) A method for processing a data stream as recited in Claim 1, wherein the unique identifier is a shortest identifier for uniquely identifying the data segment.
17. (Original) A method for processing a data stream as recited in Claim 1, wherein determining whether the data segment has been previously stored includes generating a content derived summary for the data segment; and the unique identifier is derived from the content derived summary.
18. (Original) A method for processing a data stream as recited in Claim 1, wherein determining whether the data segment has been previously stored includes generating a content derived summary for the data segment; and the unique identifier includes a value derived from the content derived summary and a serial number.
19. (Original) A method for processing a data stream as recited in Claim 1, wherein the representation of the data stream is a compressed representation.
20. (Original) A method for processing a data stream as recited in Claim 1, wherein the representation of the data stream is used for reconstructing the data stream.

21. (Original) A method for processing a data stream as recited in Claim 1, wherein determining whether the data segment has been previously stored includes generating a candidate identifier; and determining whether the candidate identifier has been stored previously.
22. (Original) A method for processing a data stream as recited in Claim 1, wherein:
determining whether the data segment has been previously stored includes generating a candidate identifier; and determining whether the candidate identifier has been stored previously;
generating a unique identifier for specifying the data segment includes modifying the candidate identifier.
23. (Currently Amended) A method for processing a data stream as recited in Claim [[1]] 22, wherein modifying the candidate identifier includes adding a value to the candidate identifier.
24. (Currently Amended) A method for processing a data stream as recited in Claim [[1]] 22, wherein modifying the candidate identifier includes combining an additional bit with the candidate identifier.
25. (Currently Amended) A method for processing a data stream as recited in Claim [[1]] 22, wherein modifying the candidate identifier includes combining a plurality of bits with the candidate identifier.
26. (Original) A method for processing a data stream as recited in Claim 1, wherein the unique identifier is stored in a reconstruction list.
27. (Original) A method for processing a data stream as recited in Claim 1, in the event that the data segment is determined to have been previously stored, further including locating a unique identifier previously assigned to the data segment.

28. (Original) A method for processing a data stream as recited in Claim 1, in the event that the data segment is determined to have been previously stored, further including locating a unique identifier previously assigned to the data segment; and the unique identifier is stored in a reconstruction list.

29. (Original) A method for processing a data stream as recited in Claim 1, further comprising:

determining whether the data segment has been previously stored; and
in the event that the data segment is determined not to have been previously stored, storing the data segment.

30. (Original) A system for processing a data stream comprising:

an interface configured to receive a data segment;

a processor coupled to the interface, configured to:

determine whether the data segment has been previously stored;

and

in the event that the data segment is determined not to have been previously stored, generate a unique identifier for specifying the data segment in a representation of the data stream.

31. (Original) A computer program product for processing a data stream, the computer program product being embodied in a computer readable medium and comprising computer instructions for:

receiving a data segment;

determining whether the data segment has been previously stored; and

in the event that the data segment is determined not to have been previously stored, generating a unique identifier for specifying the data segment in a representation of the data stream.